

# WISEASY T1

## EMV Android Tablet



Diverse Payments



Full Screen Touch Tablet with Magnetic Stand



Commercial Security Operating System



IC/Magnetic Card Reading & Writing



Multiple Interfaces for Peripheral Devices



External Printer



Biometric Features Module (Optional)



- Android 10.1 security operating system, Qualcomm Octa-core processor, running speed is greatly improved.
- Fully compatible with encrypted magnetic stripe card, financial IC card, NFC, BLE, sound wave and other payment technology.
- Full screen tablet touch experience, magnetic suction supports matching use, supports desktop + handheld multi-scene applications.
- Financial level technical security and protection threshold, anti-disassembly, anti-attack, anti-spy protection hardware and structural physical security design.
- Highly integrated industrial design, reserved with multiple USB interfaces, network ports and other interfaces on the base, can be connected to keyboard, printer and other peripherals.




Magnetic Dock Stand 1



Magnetic Dock Stand 2



Cashier Box 1



Printer M58

## Technical Specifications



### Operating System

Android 10.1, WiseOS



### CPU

Qualcomm Octa-Core  
1.8GHz



### Memory

2GB+16GB Standard  
Optional: 4GB+64GB



### Display

11.6 inches,  
resolution: 1920\*1080  
10 points touch screen



### Camera

Front camera: 5Mega  
Rear camera: 8Mega,  
Supports auto focus & flashlight



### Network

2G/3G/4G



### WIFI

2.4G/5G, 802.11 a/b/g/n/ac



### Bluetooth

BT 4.2+BLE



### GPS

GPS/AGPS/GLONASS/  
Beidou



### NFC

13.56MHz, Support EMV2.6b  
standard ISO/IEC 14443,  
ISO18092, Type A&B, Felica,  
Mifare



### IC Card Reader

1. ISO7816
2. PBOC3.0 L1/L2



### Magnetic Card Reader

ISO7810/7811, Support  
three-track two-way  
manual swinging



### Printer

Bluetooth and USB Printer



### USB Port

Type C USB2.0, High Speed,  
OTG.



### Card Slot

1 \* Micro SIM + 1 \* Micro PSAM  
or 2 \* SIM,  
Supports DSDS (SAM slot) &  
the SIM card



### Audio

Single speaker, 1.2w



### Battery

3.7v/6450mAh,  
supports fast charging



### Adapter

Input: AC 100-240V, 50/60Hz  
Output: 9V/2A



### Weight

T1: 1006g  
Bracket 1: 1200g  
Bracket 2: 1075g



### Dimensions

T1: 287.3\*180.9\*18.7 mm  
Bracket 1: 239.5\*219.5\*195.6 mm  
Bracket 1: 239.5\*219.5\*188.8 mm



### Dock Stand

#### Option 1:

Fingerprint: Optional  
RJ45: Supports RJ45, WLAN and Ethernet  
USB: 3\*Type A USB ports  
Wire Charger: DC interface, 9V/2A  
Standing Charger: Magnetic suction  
connection charging

#### Option 2:

USB: 1\*Type A USB ports  
Wire Charger: DC interface, 9V/2A  
Standing Charger: Magnetic suction  
connection charging



### Temperature

Storage temperature: -35°C to 70°C  
Operating temperature: -10°C to 55°C  
Humidity: ≤95%

## Certifications

**EMV Contact L1 / EMV Contactless L1 2.6b / EMV Contact L2 / VISA / MASTERCARD / AMEX / DISCOVER / PCI / TQM / State secret certification  
GSMA / EU CE / India BIS / Mexico NOM / RoHS / CB**